

CLAIM:

1. A method of authenticating mobile user equipment in a mobile telecommunications network comprising the steps of:
- passing an authentication element forming at least part of an authentication vector, from a serving network to mobile user equipment,
 - deciding in the user equipment based at least in part on the value of a predetermined field contained in the authentication element, when to generate a termination message, and
 - passing the termination message from the mobile user equipment to the serving network which message contains a value indicating that the serving network must obtain a further authentication vector before allowing the user equipment to make further calls.
2. A method according to claim 1, wherein the termination message is a predetermined key set identity value.
3. A method according to claim 1, wherein the predetermined field is an authentication management field.
4. A method according to claim 1, wherein the said decision is taken based on the total call duration which has accumulated since the authentication element

containing the predetermined field was first received by the mobile user equipment.

5. A method according to claim 1, wherein the said decision is taken based on the time elapsed since the authentication element containing the predetermined field was first received by the mobile user equipment.

6. A method according to claim 1, wherein the said decision is taken based on the total number of calls made since the authentication element containing the predetermined field was first received by the mobile user equipment.

7. A SIM for mobile user equipment embodying the method steps of claim 1.

8. A method of authenticating mobile user equipment in a mobile telecommunications network comprising the steps of:

requesting service from a serving network to which the user equipment is not directly subscribed,

passing the request for service from the serving network to a home operator network to which the user equipment is directly subscribed,

generating an authentication vector in the home operator network which includes an authentication management field,

543
21

0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99

passing the key set identifier to the serving network.

9. A method according to claim 8, including deciding in the user equipment based at least in part on the value of a predetermined field contained in the authentication element, when to generate a key set identifier which contains a value indicating that the serving network must obtain a further authentication vector before allowing the user equipment to make further calls.
10. A method according to claim 9, wherein the said decision is taken based on the total call duration which has accumulated since the authentication element containing the predetermined field was first received by the mobile user equipment.

11. A method according to claim 9, wherein the said decision is taken based on the time elapsed since the authentication element containing the predetermined field was first received by the mobile user equipment.
12. A method according to claim 9, wherein the said decision is taken based on the total number of calls made since the authentication element containing the predetermined field was first received by the mobile user equipment.
13. Mobile user equipment for use in a mobile telecommunications network including means for receiving from a serving network, an authentication element forming at least part of an authentication vector, decision means for deciding in the user equipment based at least in part on the value of a predetermined field contained in the authentication element, when to generate a termination message, and means for passing the termination message from the mobile user equipment to the serving network which message contains a value indicating that the serving network must obtain a further authentication vector before allowing the user equipment to make further calls.
14. Mobile user equipment according to claim 13, including accumulator means for monitoring the total call duration which has accumulated since the authentication element containing the predetermined field was first received by the mobile user

543
A1

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

equipment and providing a value representative of the said total call duration to the decision means.

15. Mobile user equipment according to claim 13, including timer means for measuring the time elapsed since the authentication element containing the predetermined field was first received by the mobile user equipment and providing a value representative of the said elapsed time to the decision means.

16. Mobile user equipment according to claim 13, including counter means for counting the total number of calls made since the authentication element containing the predetermined field was first received by the mobile user equipment and providing a value representative of the said total call number to the decision means.